

### III. CLAIM AMENDMENTS

1. (Currently Amended) A method for synchronizing a receiver (MS) to a code modulated signal transmitted by satellites (SV1-SV4), in which method information is transmitted by modulating the code modulated signal in the transmission step and demodulation is performed in the reception step for clarifying the transmitted information, and from which satellites at least partly the same information is transmitted essentially simultaneously, characterized in that in the method the signal transmitted by two or more satellites is received, the transit time differences of the received signals are determined for mutual synchronization of the signals transmitted from different satellites, and an analysis signal is formed by using at least a part of at least two synchronized signals received from different satellites wherein the analysis sample string is formed by combining only those parts of the at least two synchronized signals that are common to each other.

2. (Original) A method according to Claim 1, characterized in that reference information is formed, and said reference information is compared to said analysis signal for finding at least one said signal, which contains the same information.

3. (Original) A method according to Claim 2, characterized in that correlation is used in the comparison.

4. (Previously Presented) A method according to claim 1, in which the information to be transmitted is sent in one or more

data frames (SF1-SF5), and at least one data frame (SF1-SF5) includes at least an initial synchronization part (preamble, P), characterized in that the preamble (P) is searched from the analysis signal in the method.

5. (Previously Presented) A method according to claim 1, in which the information to be transmitted is sent in one or more data frames (SF1-SF5), and at least one data frame (SF1-SF5) includes at least time data (TOW), characterized in that said time information (TOW) is searched from the analysis signal in the method.

6. (Previously Presented) A method according to claim 1, in which the information to be transmitted is sent in one or more data frames (SF1-SF5), and at least one data frame (SF1-SF5) includes at least identification information (ID), characterized in that said identification information (ID) is searched from the analysis signal in the method.

7. (Previously Presented) A method according to claim 1, in which the information to be transmitted includes at least ephemeris data, characterized in that said ephemeris data is used in the method for determining the location of the receiver.

8. (Previously Presented) A method according to claim 1, characterized in that the information to be modulated in the method is binary information, and thus the information to be modulated consists of a number of information bits, each of which has either the first or the second binary value.

9. (Original) A method according to Claim 8, characterized in that the code used in the modulation is formed of a set of chips, on the basis of the code either a first or a second value is selected for each chip, whereupon a signal modulated with said set of chips forms an epoch, that at least one of said epochs is used in the transmission of each information bit, and that the modulation is carried out so that if the value of the information bit to be modulated is the first binary value, values selected for the chips of said epoch are used in the modulation, or if the value of the information bit is the second binary value, the value opposite to the value selected for each chip of the epoch is used in the modulation.

10. (Original) A receiver (MS), which comprises at least synchronization means (3, 4, 7, 16) for synchronizing the receiver (MS) to the code modulated signal transmitted by the satellites (SV1-SV4), and demodulation means (1, 2a-2d, 5) for clarifying the transmitted information, and from which satellites at least partly the same information has been transmitted essentially simultaneously, characterized in that the receiver (MS) also comprises means (1, 2a-2d) for receiving the signal transmitted by two or more satellites (SV1-SV4), and that said synchronization means comprise at least means (7, 10, 11) for determining the transit time differences of the received signals, means (3) for synchronizing the received signals of different satellites (SV1-SV4) for mutual synchronization of the signals on the basis of said transit time differences, and means (3, 4) for forming an analysis signal by using at least part of at least two synchronized signals received from different satellites (SV1-SV4).

11. (Original) A receiver (MS) according to Claim 10, characterized in that it also comprises at least means (16) for forming at least one piece of reference information, and comparison means (7, 8) for comparing said reference information to said analysis signal for finding at least one said signal, which contains the same information.

12. (Original) A receiver (MS) according to Claim 10, characterized in that the comparison means comprise means (7) for performing correlation between said reference information and said analysis signal.

13. (Previously Presented) A receiver (MS) according to claim 10, in which the information to be transmitted has been sent in one or more data frames (SF1-SF5), and at least one data frame (SF1-SF5) includes at least an initial synchronization part (preamble, P), characterized in that said comparison means comprise means (3, 4) for searching said preamble (P) from the analysis signal.

14. (Previously Presented) A receiver (MS) according to claim 10, in which the information to be transmitted has been sent in one or more data frames (SF1-SF5), and at least one data frame (SF1-SF5) includes at least time data (TOW), characterized in that said comparison means comprise means (3, 4) for searching said time data (TOW) from the analysis signal.

15. (Previously Presented) A receiver (MS) according to claim 10, in which the information to be transmitted has been sent in one or more data frames (SF1-SF5), and at least one data

frame (SF1-SF5) includes at least identification information (ID), characterized in that said comparison means comprise means (3, 4) for searching said identification information (ID) from the analysis signal.

16. (Previously Presented) A receiver (MS) according to claim 10, in which the information to be transmitted includes at least ephemeris data, characterized in that the receiver also comprises means (3, 4, 7, 8) for using said ephemeris data for determining the location of the receiver (MS).

17. (Previously Presented) A receiver (MS) according to claim 10, characterized in that the information to be modulated is binary information, and thus the information to be modulated consists of a number of information bits, each of which has either the first or the second binary value.

18. (Original) A receiver (MS) according to Claim 17, characterized in that the code used in the modulation has been formed of a set of chips, on the basis of the code either a first or a second value has been selected for each chip, whereupon an epoch has been formed of a signal modulated with said set of chips, that at least one of said epochs has been used in the transmission of each information bit, and that the modulation has been carried out so that if the value of the information bit to be modulated is the first binary value, values selected for the chips of said epoch have been used in the modulation, or if the value of the information bit is the second binary value, the

value opposite to the value selected for each chip of the epoch has been used in the modulation.

19. (Original) A positioning system, which comprises at least:

two or more satellites (SV1-SV4), which comprise means for transmitting a code modulated signal, and means for transmitting information by modulating said code modulated signal, and

a receiver (MS), which comprises synchronization means (3, 4, 7, 16) for synchronizing the receiver (MS) to the code modulated signal transmitted by the satellites (SV1-SV4), and demodulation means (1, 2a-2d, 5) for clarifying the transmitted information,

and from which satellites at least partly the same information has been arranged to be transmitted essentially simultaneously, characterized in that the receiver (MS) also comprises means (1, 2a-2d) for receiving the signal transmitted by two or more satellites (SV1-SV4), means (2a-2d) for determining the transit time differences of the received signals, and that said synchronization means comprise at least means (7, 10, 11) for determining the transit time differences of the received signals, means (3) for mutual synchronization of the received signals of different satellites (SV1-SV4) on the basis of said transit time differences, and means (3, 4) for forming an analysis signal by using at least part of at least two synchronized signals received from different satellites (SV1-SV4).

20. (New) The method of claim 1 further comprising a cross-correlation of the received signal to a known data sequence out to correct transmit time differences without using any auxiliary data from a network.